





REQUIREMENTS OF THE BICYCLES		
ADULT BIKE		
Wheel diameter	Minimum size: 635 mm (25")	
Diameter and characteristics of the seat-post tube	Min 25.4 mm (1"), Max 31.8 mm (1.25")	
Precautions for use	<b>The use of non-metal seat posts is forbidden.</b> Accessories or parts that may interfere with the operation of the tow-bar must never be used.	
CHILD BIKE		
Wheel diameter	Minimum wheel size: Min 255 mm (10") Max 510 mm (20")	
Diameter and characteristics of the handlebar columns	Diameter min. 34mm (1.34"), max 38mm (1.50"). Ensure that the brake cable does not interfere with the child bike tow-bar connector.	
Precautions for use	If the bike is fitted with stabilizer wheels: turn them upwards or remove them altogether before using the child bike with the tow-bar. Accessories or parts that may interfere with the operation of the tow-bar must never be used.	
REQUIREMENTS FOR THE CYCLISTS		
ADULT CYCLIST		
Basic skill	Must be an adult and able to ride a bicycle with complete mastery of the same.	
Equipment	Must wear a helmet approved in accordance with the regulations in force.	
CHILD CYCLIST		
Basic skill	The child must be able to grip the handlebar properly and, in any case, demonstrate a certain confidence in riding the bike and be capable of pedalling properly.	
Equipment	The child must wear a helmet approved in accordance with the rules in force while the use of adequate protection for the knees and elbows is also recommended. Make sure that the child wears clothing that is suitable for the weather conditions, in particular, make sure the child is suitably protected in the event of rain.	
PERMISSIBLE MAXIMUM WEIGHTS		
Adult's weight		Must have sufficient weight for towing (minimum double the child's weight)
Child's weight		Max 30 kg (66.14 lb)
Child bike weight		Max 15 kg (33.07 lb)
Child bike weight + child's weight		In any case the towed weight must not exceed 45 kg (99.21 lb)