
TOTAL CLASSIC 5W-40





"TOTAL CLASSIC, the guaranteed quality"

Synthetic technology multigrade oil for gasoline and Diesel engines, formulation using a set of additives with carefully selected performance and proportions to answer to the quality standards of the Association of the European Manufacturers (ACEA).

APPLICATIONS

All gasoline/Diesel engines Direct injection Diesel	•	Recommended for all gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines – with or without turbocharging – in cars and light vans
Direct injection Diesel	•	Particularly recommended to meet the requirements of Diesel engines with direct injection.
The most severe journeys All times of year	•	Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions
"Vigorous" driving	•	For all driving styles, particularly "vigorous" and high speeds.
Pofor to the maintenance book of your yob	iclo to	know the recommendation of the manufacturer

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

PERFORMANCES

International specifications	ACEA API	A3/B4 SL/CF

1

CUSTOMER BENEFITS

High performance

- Excellent engine protection, particularly against timing system wear .
- Lengthens engine life

- Immediate lubrication of engine parts during cold starts, leading to longer engine life
- Extended oil change intervals . TOTAL CLASSIC 5W-40 meets the requirements of the manufacturers as regards extended oil change intervals.

CHARACTERISTICS

TOTAL CLASSIC	Units	SAE Grade 5W-40	
5W-40			
Density at 15°C	kg/m ³	853	
Viscosity at 40°C	mm²/s	85	
Viscosity at 100°C	mm²/s	14	
Flash point Cleveland	C	228	
Pour point	C°	- 39	

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le Spazio, 562 avenue du Parc de l'ile 92029 Nanterre Cedex FRANCE 1/1

TOTAL CLASSIC 5W-40 Sheet updated : 02/14



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.