



Plug No.	Outer size	Inner size	Output voltage	Compatibility
1	6.5	4.4	16 V	SONY: 16 V/4 A; SONY: 16 V/3.75 A; Fujitsu: 16 V/3.36 A; Fujitsu: 16 V/3.75 A
2	6.5	4.4	18.5 V/19 V/19.5 V	Fujitsu: 19 V/3.16 A; SONY: 19.5 V/2.15 A; SONY: 19.5 V/3 A; SONY: 19 V/3.16 A
3	6.3	3.0	15 V	Toshiba: 15 V/5 A; NEC: 15 V/4 A; Toshiba: 15 V/3 A; Toshiba: 15 V/4 A
4	5.5	2.5	16 V	IBM/Lenovo: 16 V/3.36 A; IBM/Lenovo: 16 V/3.5 A; IBM/Lenovo: 16 V/4.5 A
5	5.5	2.5	18.5 V/19 V	NEC: 19 V/3.16 A; Lite-On: 19 V/3.16 A, 3.42 A; Delta: 19 V/3.42 A; Toshiba: 19 V/3.42 A, 3.16 A; Acer: 19 V/3.16 A, 3.42 A; ASUS: 19 V/3.42 A; HP/Compaq: 19 V/1.1 A, 3.16 A, 3.42 A; ASUS: 19 V/3.42 A; Dell: 19 V/3.16 A; LS: 20 V/3.25 A; Gateway: 19 V/3.16 A, 3.68 A; Lenovo: 19 V/3.42 A, 3.16 A; Fujitsu: 19 V/3.16 A
7	5.5	1.7	18.5 V/19 V	Acer: 19 V/1.58 A, 3.42 A, 4.74 A; Dell: 19 V/1.58 A; HP: 19 V/1.58 A
8	4.8	1.7	18.5 V/19 V	ASUS: 19 V/2.1 A; Compaq: 18.5 V/2.7 A; Compaq: 18.5 V/3.8 A; HP/Compaq: 18.5 V/3.5 A; LG: 18.5 V/3.5 A; Delta: 19 V/2.64 A; Asus: 19 V/2.64 A; NEC: 19 V/2.64 A
9	7.4	5.0	19 V/19.5 V	Dell: 19.5 V/3.34 A; Dell: 19.5 V/2.64 A
10	7.4	5.0	18.5 V/19 V	HP/Compaq: 18.5 V/3.5 A
11	5.5	2.1	19 V	Acer: 19 V/3.16 A; Acer: 19 V 3.42 A
15	7.9	5.5	20 V	IBM/Lenovo: 20 V/3.25 A