

MOTO SNOW

4T 0W30

SNOW



Lubricants

Description

Synthetic lubricant oil for snow vehicles driven by 4-stroke engines and developed to meet the demands of the main manufacturers. It displays excellent behaviour at low temperatures thanks to its low viscosity; it enables the engine to develop maximum performance in intense cold or when there is snow, and it achieves perfect lubrication of the different engine elements in extreme environmental conditions.

Properties

- Low pour point, allowing its use under temperatures below zero.
- Its carefully researched viscosity provides a smooth flow at low temperatures, maintaining the lubricating film and the level of protection required for engines at these temperatures.
- Its modern formula endows this oil with magnificent antiwear, dispersant and antioxidant properties, preventing the formation of sludge and improving the engine's performance.

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			0W30
Density at 15 °C	g/mL	ASTM D 4052	0.850
Viscosity at 100 °C	cSt	ASTM D 445	11.0
Viscosity at 40 °C	cSt	ASTM D 445	60
Viscosity at -35 °C	cP	ASTM D 5293	6200 max.
Viscosity index	-	ASTM D 2270	176
Flash point, open cup	°C	ASTM D 92	205 min.
Pour point	°C	ASTM D 97	-48 max.
TBN	mg KOH/g	ASTM D 2896	6.8
Sulphated ashes	% in weight	ASTM D 874	0.9
Bosch Injector Shearing: Viscosity at 100 °C after shear	cSt	CEC-L014-93	10.98

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. October 2010.