

**Product : CORROSION PROTECTION SPRAY**

**VAC Ref. nr : BL020663**

**Composition :** A mixture of solvents and active concentrate.  
Propellant : Butane/Propane.

**Dangerous components (conform MSDS) :**

| Name Component  | Concentration Range |
|---|---------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics | > 50 < 100 %        |
| Distillates (petroleum), hydrotreated light paraffinic                | > 10 < 25 %         |
| Distillates (petroleum), hydrotreated heavy paraffinic                | > 10 < 25 %         |
| Butane (< 0,1 % 1,3-Butadiene)  | > 10 < 25 %         |
| Propane   | > 2.5 < 10 %        |
| Isobutane   | > 2.5 < 10 %        |
| Benzenesulfonic acid, di-C10-14-alkyl derivs, calcium salts           | > 0 < 1 %           |

**Technical data :**

Density aerosol (20 °C) : ± 0.726 g/ml

Pressure aerosol (20°C) : ± 3.0 bar

**Application :**

Loosens rust and protects against moisture and oxidation. Only use the product conform the instructions on the aerosol.

**Directions for use :**

Store and use at room temperature. Clean and dry the surfaces to be treated. Spray from a distance of 20 cm, holding the can upright. Apply a thin coating. Repeat treatment regularly for optimum protection. It is ideal for use in high humidity and high salt environments and can be used safely on painted or lacquered surfaces, metals and plastics.

**Hazard pictograms :**



**Signal Word :**

Danger



# TECHNICAL DATA SHEET

## CORROSION PROTECTION SPRAY

Page 2 of 2

Reference nr

**BL020663**

Date of edition

**08/11/21**

### **Product identifiers :**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2 % aromatics

### **Hazard statements :**

H222 : Extremely flammable aerosol.  
H229 : Pressurised container: May burst if heated.  
H336 : May cause drowsiness or dizziness.

### **Precautionary statements :**

P101 : If medical advice is needed, have product container or label at hand.  
P102 : Keep out of reach of children.  
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 : Do not spray on an open flame or other ignition source.  
P251 : Do not pierce or burn, even after use.  
P271 : Use only outdoors or in a well-ventilated area.  
P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P405 : Store locked up.  
P501 : Dispose of container to an approved waste disposal plant.

### **Required additional information :**

EUH208 : Contains Benzenesulfonic acid, di-C10-14-alkyl derivs, calcium salts. May produce an allergic reaction.

### **Other hazards :**

Intentional misuse of the preparation by concentrating and breathing vapour could be harmful or fatal.