



TECHNICAL DATA SHEET

ADHESIVE CHAIN LUBRICANT

Page 1 of 2

Reference nr

093850

Date of edition

27/10/21

Product : ADHESIVE CHAIN LUBRICANT

VAC Ref. nr : 093850

Composition : A mixture of solvents and active concentrate.
Propellant : Butane/Propane.

Dangerous components (conform MSDS) :

Name Component	Concentration Range
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	≥ 25 < 50 %
Hydrocarbons, C6, isoalkanes, < 5 % n-hexane	≥ 25 < 50 %
Butane (< 0.1% 1,3-Butadiene)	≥ 10 < 25 %
Propane	≥ 10 < 25 %
Isobutane	≥ 2.5 < 10 %
n-Hexane	≥ 1 < 2.5 %
Cyclohexane	≥ 0 < 1 %
Alkanes C14-17, chloro	≥ 0 < 1 %

Technical data :

Density aerosol (20 °C) : ± 0.650 g/ml

Pressure aerosol (20°C) : ± 3.5 bar

Application :

Lubricant. Only use the product conform the instructions on the aerosol.

Directions for use :

Store and use at room temperature. Shake well before use. Spray from a distance of 20 cm, holding the can upright.

Hazard pictograms :



Signal Word :

Danger

Product identifiers :

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C6, isoalkanes, < 5 % n-hexane

Volcke Aerosol Company NV

B-8520 KUURNE TEL.: +32 (0) 56 35 17 23



TECHNICAL DATA SHEET

ADHESIVE CHAIN LUBRICANT

Page 2 of 2

Reference nr

093850

Date of edition

27/10/21

Hazard statements :

- H222 : Extremely flammable aerosol.
- H229 : Pressurised container: May burst if heated.
- H315 : Causes skin irritation.
- H336 : May cause drowsiness or dizziness.
- H410 : Very toxic to aquatic life with long lasting effects.

Precautionary statements :

- P101 : If medical advice is needed, have product container or label at hand.
- P102 : Keep out of reach of children.
- P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 : Do not spray on an open flame or other ignition source.
- P251 : Do not pierce or burn, even after use.
- P271 : Use only outdoors or in a well-ventilated area.
- P273 : Avoid release to the environment.
- P391 : Collect spillage.
- P405 : Store locked up.
- P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- P501 : Dispose of container at an approved waste disposal plant.

Other hazards :

Intentional misuse of the preparation by concentrating and breathing vapour could be harmful or fatal.