



TECHNICAL DATA SHEET

ANTI-RAIN SPRAY

Page 1 of 2

Reference nr

093149

Date of edition

01/02/22

Product : ANTI-RAIN SPRAY

VAC Ref. nr : 093149

Composition : A mixture of solvents and active concentrate.
Propellant : Butane/Propane.

Dangerous components (conform MSDS) :

Name Component	Concentration Range
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	≥ 25 < 50 %
Hydrocarbons, C6, isoalkanes, < 5 % n-hexane	≥ 25 < 50 %
Propan-2-ol	≥ 10 < 25 %
n-Butyl acetate	≥ 2.5 < 10 %
Butane (≤ 0.1 % butadiene)	≥ 2.5 < 10 %
Monopropylene glycol methyl ether	≥ 2.5 < 10 %
Propane	≥ 2.5 < 10 %
Isobutane	≥ 2.5 < 10 %
Ethylacetate	≥ 1 < 2.5 %
n-Hexane	≥ 1 < 2.5 %
Cyclohexane	≥ 0 < 1 %
2-Methoxy-1-propanol	≥ 0 < 1 %

Technical data :

Density aerosol (20 °C) : ± 0.688 g/ml
Pressure aerosol (20°C) : ± 2.0 bar

Application :

Makes the material waterproof and gives protection against most stains. Only use the product conform the instructions on the aerosol.

Instructions of use :

Store and use at room temperature. For application to textiles and different types of leather, such as suede, daim, nubuck. Ensure that the material to be treated is clean and dry. Spray at short intervals from a distance of 20 cm, holding the can upright. After leaving to dry for about an hour, the material is again ready to be used, having been made thoroughly dirt resistant and water repellent. Use preferably in open air or in a well-ventilated area. Repeat treatment frequently for optimal effect. Always first test for color fastness and resistance in an inconspicuous place. Not suitable for imitation and patent leather. Harmful on inhalation. Spray in short intervals and for short periods only. Large leather and fabric surfaces shall preferably be sprayed outdoors. Ventilate well after use.

Hazard pictograms :



Signal Word :

Danger

Product identifiers :

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C6, isoalkanes, < 5 % n-hexane
Propan-2-ol
n-Butyl acetate

Hazard statements :

H222 : Extremely flammable aerosol.
H229 : Pressurised container: May burst if heated.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

Precautionary statements :

P101 : If medical advice is needed, have product container or label at hand.
P102 : Keep out of reach of children.
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 : Do not spray on an open flame or other ignition source.
P251 : Do not pierce or burn, even after use.
P271 : Use only outdoors or in a well-ventilated area.
P273 : Avoid release to the environment.
P391 : Collect spillage.
P405 : Store locked up.
P410 + P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 : Dispose of container at an approved waste disposal plant.

Other hazards :

Intentional misuse of the preparation by concentrating and breathing vapour could be harmful or fatal.