

Key **Features**

- Ultralight 1kg design with sleek metal casing
- Adjustable kickstand from 0 to 62 degree
- AMD FreeSync Premium
- 144Hz Refresh Rate
- Diverse connectivity with USB Type-C and mini-HDMI



Product **Description**

The ViewSonic VX1755 Full HD IPS-panel portable monitor is the latest in portable gaming displays. With AMD FreeSync Premium and a 144 Hz refresh rate, gamers on the go can get the best experience wherever they play. A versatile kickstand makes it easy to set up anywhere for single-player and multiplayer sessions. The ultralight 1 kg design is supremely portable while a robust metal casing will make sure the screen survives the trip. Having both USB-C and mini-HDMI ports enable use with gaming devices ranging from consoles to laptops, connecting to both data and power easily.

Visit Us www.viewsonic.com

DISPLAY		WEIGHT (IMPERIAL)	
Display Size (in.):	17	Net (lbs):	2.2
Viewable Area (in.):	17.2	Net Without Stand (lbs):	2.2
Panel Type:	IPS Technology	Gross (lbs):	4.9
Resolution:	1920 x 1080	WEIGHT (METRIC)	
Resolution Type:	FHD (Full HD)	Net (kg):	1
Static Contrast Ratio:	800:1 (typ)	Net Without Stand (kg):	1
Dynamic Contrast Ratio:	80M:1	Gross (kg):	2.2
Light Source:	LED	DIMENSIONS (IMPERIAL) (W	
Brightness:		Packaging (in.):	19.5 x 15.6 x 3
	250 cd/m² (typ)	Physical (in.):	15.6 x 9.7 x 0.7
Colors:	16.7M	Physical Without Stand (in.):	15.6 x 9.7 x 0.7
Color Space Support:	8 bit (6 bit + FRC)	DIMENSIONS (METRIC) (WXHXD)	
Aspect Ratio:	16:9	Packaging (mm):	495 x 395 x 77
Response Time (Typical GTG):	4ms	Physical (mm):	396 x 247 x 17
Viewing Angles:	170° horizontal, 170° vertical	Physical Without Stand (mm):	396 x 247 x 17
Backlight Life (Hours):	15000 Hrs (Min)	GENERAL	000 X 247 X 17
Curvature:	Flat	GENTEROLE	CTUVus, FCC-B, ICES003, Energy Star, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
Refresh Rate (Hz):	144	Regulations:	
Adaptive Sync:	FreeSync		
Blue Light Filter:	Yes		UkrSEPRO, UKCA
Color Gamut:	NTSC: 45% size (Typ) sRGB: 64% size (Typ)	PACKAGE CONTENTS:	VX1755 x1, mini HDMI to HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Protect cover x1
Pixel Size:	0.199 mm (H) x 0.199 mm (V)		
Surface Treatment:	Anti-Glare, Hard Coating (3H)		
COMPATIBILITY		Daniela/Diagraph	Please dispose of in accordance with
PC Resolution (max):	1920x1080	Recycle/Disposal:	local, state or federal laws.
Mac® Resolution (max):	1920x1080	Warranty:	*Warranty offered may differ from market to market
PC Operating System:	Windows 11 certified; macOS tested	Power Management:	Energy Star standards
Mac® Resolution (min):	1920x1080	r oner management.	Energy of an evaluation
CONNECTOR			
USB 3.2 Type C DisplayPort Alt mode only :	1		
3.5mm Audio Out:	1		
Mini HDMI:	1		
Power in:	USB Type C (power only)		
AUDIO			
Internal Speakers:	0.8Watts x2		
POWER			
Eco Mode (Conserve):	10W		
Eco Mode (optimized):	11W		
Consumption (typical):	12W		
Consumption (max):	13W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
CONTROLS			
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
Frequency Horizontal:	mini HDMI (v2.0): 24 ~ 165KHz, Type C: 165 ~ 165KHz		
Frequency Vertical:	mini HDMI (v2.0): 48 ~ 144Hz, Type C: 48 ~ 144Hz		
VIDEO INPUT	TMDS - mini HDMI (v2.0), Micro-		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.

20° / 62°

ERGONOMICS
Tilt (Forward/Back):