

ViewSonic® LCD DISPLAY

VP3256-4K

Key Features

- **Lifelike True Beauty:** International color standard Pantone validated and 100% sRGB wide color gamut
- **Precise Color:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 color accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 2.0, DisplayPort 1.4, USB3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 4K UHD(3840* 2160) resolution IPS panel with 32" frameless design



Product Description

Designed with creative professionals in mind, the ViewSonic VP3256-4K delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us  www.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Brightness:	350 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + A-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Adaptive Sync:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	Adobe RGB: 95% size / 82% coverage (Typ) DCI-P3: 95% size / 90% coverage (Typ) EBU: 127% size / 100% coverage (Typ) REC709: 128% size / 100% coverage (Typ) SMPTE-C: 139% size / 100% coverage (Typ) NTSC: 91% size (Typ) sRGB: 128% size / 100% coverage (Typ)
Pixel Size:	0.182 mm (H) x 0.182 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	3Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	32W
Eco Mode (optimized):	39W
Consumption (typical):	46W
Consumption (max):	50W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
Cable Organization:	Yes

CONTROLS

Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 136KHz
Frequency Vertical:	24 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet - Type C
---------------	---

ERGONOMICS

Height Adjust (mm):	130
Swivel:	120°
Tilt (Forward/Back):	-5° / 21°
Pivot (Right/Left):	90° / 90°

WEIGHT (IMPERIAL)

Net (lbs):	24
Net Without Stand (lbs):	15.8
Gross (lbs):	33.7

WEIGHT (METRIC)

Net (kg):	10.9
Net Without Stand (kg):	7.2
Gross (kg):	15.3

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	33.1 x 20.5 x 12.8
Physical (in.):	28.2 x 20.23~25.35 x 10.4
Physical Without Stand (in.):	28.2 x 16.7 x 2.6

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	840 x 520 x 326
Physical (mm):	715 x 513.8~643.8 x 265
Physical Without Stand (mm):	715 x 423 x 66

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, CCC, China RoHS, China Energy Label, CECP
PACKAGE CONTENTS:	VP3256-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT