Optix G27C4

SEE BEYOND THE GAME. VISUALIZE YOUR VICTORY.





SPECIFICATIONS

Panel Resolution 1920 x 1080 (FHD) Refresh Rate 165Hz Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 10000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V)<	Panel Size	27" (69cm)
Brightness (nits) 250 nits Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 61	Panel Resolution	1920 x 1080 (FHD)
Viewing Angle 178° (H) / 178° (V) Aspect Ratio 16:9 Curvature 1500R Contrast Ratio 3000:1 Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power Type External Adaptor 20V 2.25A Power Consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° <t< th=""><th>Refresh Rate</th><th>165Hz</th></t<>	Refresh Rate	165Hz
Aspect Ratio 16:9	Brightness (nits)	250 nits
Curvature 1500R Contrast Ratio 3000:1 Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes N	Viewing Angle	178° (H) / 178° (V)
Contrast Ratio 3000:1 Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Aspect Ratio	16:9
Active Display Area (mm) 597.888(H) x 336.312(V) Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 10000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note	Curvature	1500R
Pixel Pitch (H x V) 0.3114(H) x 0.3114(V) Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Contrast Ratio	3000:1
Surface Treatment Anti-glare Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Active Display Area (mm)	597.888(H) x 336.312(V)
Display Colors 16.7M DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Pixel Pitch (H x V)	0.3114(H) x 0.3114(V)
DCI-P3 / sRGB 90% / 115% Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.7 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Surface Treatment	Anti-glare
Response time 1ms Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.7 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Display Colors	16.7M
Video ports 1x DP (1.2a) 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.7 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	DCI-P3 / sRGB	90% / 115%
Video ports 2x HDMI (1.4b) Panel Type VA Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Response time	1ms
Audio ports 1x Earphone out Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 1000000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Video ports	, ,
Kensington Lock Yes VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Panel Type	VA
VESA Mounting 100 x 100 mm Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Audio ports	1x Earphone out
Control 5-way OSD navigation joystick Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Kensington Lock	Yes
Power Input 100~240V, 50~60Hz DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	VESA Mounting	100 x 100 mm
DCR 100000000:1 Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Control	5-way OSD navigation joystick
Power Type External Adaptor 20V 2.25A Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Power Input	100~240V, 50~60Hz
Power consumption 30W Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	DCR	100000000:1
Signal Frequency 53.28 to 183.15KHz (H) 48 to 165Hz (V) Adjustment (Tilt) -5° ~ 20° Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Power Type	External Adaptor 20V 2.25A
Adjustment (Tilt)	Power consumption	30W
Dimension (W x H x D) 611.5 x 457.9 x 225.4 mm / 24.08 x 18.23 x 8.87 inch Console Mode FHD @ 120Hz Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Signal Frequency	
Substitute	Adjustment (Tilt)	-5° ~ 20°
Weight (NW / GW) 5.4kg / 9.0kg 11.9lbs / 19.84lbs Frameless Design Yes Note Display Port: 1920 x 1080 (Up to 165Hz)	Dimension (W x H x D)	
11.9lbs / 19.84lbs	Console Mode	FHD @ 120Hz
Display Port: 1920 x 1080 (Up to 165Hz)	Weight (NW / GW)	
	Frameless Design	Yes
HDMI: 1920 X 1080 (Up to 144Hz)	Note	Display Port: 1920 x 1080 (Up to 165Hz) HDMI: 1920 x 1080 (Up to 144Hz)

FEATURES



Curved Gaming

MSI Curved Gaming Monitor will give you the most immersive and competitive edge you need to take down your opponents.

Radeon FreeSync™



Puts an end to choppy gameplay and broken frames with fluid, artifact-free performance at virtually any framerate.



Curved Gaming™



View more of your game. MSI Curved Gaming $^{\mathtt{m}}$ monitors are perfect for gamers to play their games.

165Hz High Refresh Rate

Experience smooth gaming with a blazing fast 165Hz refresh rate, that gives you the upperhand in fast moving games



1ms Fast Response Time

Eliminate screen tearing and choppy frame rates with 1ms response time.



Frameless Design

With the narrow bezel, you will not even notice the monitor at all in the heat of the moment.



Wide Color Gamut

Wide Color Game colors and details will look more realistic and refined, to Gamut push game immersion to its limits.



MONITOR

Optix G27C4

SEE BEYOND THE GAME. VISUALIZE YOUR VICTORY.

CONNECTIONS



© 2023 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

- 1. 5-way joystick navigator
- 2. 1x DC Jack
- 3. 2x HDMI 1.4b
- 4. 1x Display Port 1.2a
- 5. 1x Earphone out
- 6. 1x Kensington lock