

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Autoprofi OXICAT Hybrid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaner for car catalyts

1.3. Details of the supplier of the safety data sheet

Company name:	CTP GmbH	
Street:	Saalfelder Strasse 35h	
Place:	D-07338 Leutenberg	
Telephone:	+49 (0)36734 230-0	Telefax: +49 (0)36734 230-22
e-mail:	msds@bluechemgroup.com	
Contact person:	Jens Moeller, Dipl.-Chem.	Telephone: +49 (0)36734 230-19
Internet:	www.bluechemgroup.com	

1.4. Emergency telephone number:

GBK GmbH: +49-(0)6132-84463 (24/7)

Further Information

Article Number: 43934

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Harmful if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

2-ethyl-hexanol

Benzyl alcohol

Signal word: Danger

Pictograms:



Hazard statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 2 of 8

H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe vapour/aerosole.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves and eye/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Solvent mixture

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics			25 - < 35 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
104-76-7	2-ethyl-hexanol			30 - < 40 %
	203-234-3		01-2119487289-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H332 H315 H319 H335			
100-51-6	Benzyl alcohol			28 - < 38 %
	202-859-9		01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move victim to fresh air. Put victim at rest and keep warm.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

In case of difficulties of breathing consult physician.

If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes.

After contact with skin, wash immediately with plenty of water and soap.

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 3 of 8

Rub greasy ointment into the skin.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
Consult physician.

After ingestion

Let water be drunken in little sips (dilution effect). Consult physician.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.
After ingestion: Harmful: may cause lung damage if swallowed.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder.
Sand.
alcohol resistant foam.
Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Formation of decomposition products possible.
In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Cool endangered container in case of fire.
Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of fire: Wear self-contained breathing apparatus.

6.2. Environmental precautions

Beat down gas/vapours/mist with water spray.
Do not empty into drains or the aquatic environment.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spreading of spillages (e.g. by oil barrier).
Wipe up with absorbent material (eg. cloth, fleece).

6.4. Reference to other sections

No data

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Closed devices. Vapours / aerosols must be extracted by suction immediately at point of origin.

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 4 of 8

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Wash hands before breaks and after work.

Eye/face protection

Wear tightly sealed safety glasses against possible splashes into the eyes. (DIN EN 166)

Hand protection

Tested protective gloves are to be worn: Butyl rubber. (DIN EN 374)

Skin protection

Wear suitable solvent-proof protective clothing according to EN 465.

Respiratory protection

In case of accumulation of fumes/aerosols, provide adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear/colourless
Odour:	characteristic

Test method

Changes in the physical state

Flash point:	~70 °C	DIN EN ISO 2719
Density (at 20 °C):	0,88 g/cm ³	DIN 51757
Water solubility: (at 20 °C)	insoluble	

9.2. Other information

No data

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 5 of 8

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidizing agents.
acid, concentrated.
Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Carbon monoxide (CO).
Carbon dioxide (CO₂).
aldehydes

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix calculated

ATE (inhalative vapour) 16,67 mg/l; ATE (inhalative aerosol) 3,345 mg/l

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 5000 mg/kg	Rabbit		
	inhalative (4 h) gas	LC50 >5 ppm	Rat		
104-76-7	2-ethyl-hexanol				
	oral	LD50 2047 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rat		
	inhalative vapour	ATE 11 mg/l			
	inhalative aerosol	ATE 1,5 mg/l			
100-51-6	Benzyl alcohol				
	oral	LD50 1230 mg/kg	Rat		
	dermal	LD50 2000 mg/kg	Rabbit		
	inhalative vapour	ATE 11 mg/l			
	inhalative (4 h) aerosol	LC50 >4,178 mg/l	Rat		

Irritation and corrosivity

After skin contact: Frequently or prolonged contact with skin may cause dermal irritation.
Irritation of eyes: Irritant effect possible.

SECTION 12: Ecological information

12.1. Toxicity

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 6 of 8

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics					
	Acute fish toxicity	LC50 mg/l	1000	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1000	48 h	Daphnia magna (Big water flea)	
104-76-7	2-ethyl-hexanol					
	Acute fish toxicity	LC50 mg/l	17,1	96 h	Leuciscus idus	
	Acute algae toxicity	ErC50	11,5 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	39 mg/l	48 h	Daphnia magna	
100-51-6	Benzyl alcohol					
	Acute fish toxicity	LC50	460 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	640 mg/l	96 h	Scenedesmus quadricauda	
	Acute crustacea toxicity	EC50	400 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not dispose with household waste.

Do not empty into drains or the aquatic environment.

Have to add a Special treatment in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Arrange about the exact waste code with the local waste disposal expert.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.

Do not pierce, cut up or weld unclean container. (Explosion hazard.)

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

-

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 7 of 8

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Other applicable information (land transport)

No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

Other applicable information (marine transport)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)

Other applicable information (air transport)

No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C10-C13, n-Alkanes, Isoalkanes, Cyclics, < 2% Aromatics

Additional information

Contains: (Regulation (EC) No. 648/2004 (Detergents regulation))

> 30 % hydrocarbons, aliphatic.

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

Additional information

Regarding the EU-directive 2008/105/EU contains the product none of the listed substances.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method

according to Regulation (EC) No 1907/2006

Autoprofi OXICAT Hybrid

Revision date: 19.04.2018

Product code: 2068

Page 8 of 8

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

OXICAT Oxygen Sensor and Catalytic Converter Cleaner Hybrid Autoprofi

Product properties

Hybrid OXICAT is a specially developed high-performance cleaner that removes deposits, soot and carbon residues in the entire exhaust tract, especially in the area of the catalytic converter, the lambda sensor, the turbocharger and the EGR valve in a sustainable and effective manner. The product is highly effective in combating problems such as operational pollutants and increased emissions resulting from the frequent occurrence of hybrid vehicle combustion engines in the cold start phase due to irregular short-term operation. When used regularly, Hybrid OXICAT provides protection against re-contamination as well as increases fuel efficiency, optimizes engine performance, and ensures proper functionality of the catalytic converter and the lambda sensor. Thus, the cleaner supports compliance with the emission limit values.

ADVANTAGES

- Removes existing deposits
- Provides protection against heavy pollution in case of irregular short-time operation of the engine
- Restores engine performance
- Ensures the proper functionality of the Lambda sensor/ Catalyst/ Turbocharger and the EGR valve
- Prevents or eliminates problems displayed via on board diagnostics / OBD

Area of application

For use in all hybrid vehicles with petrol and diesel engines. Recommended use in vehicles that did not pass the emissions test (part of the main investigation) due to excessive exhaust emissions.

Application

Regularly every 3-4 months to admit the fuel tank. Observe mixing ratio!

Consumption

250 ml or up to 60-80 liter fuel. Mixing Ratio: 1:300

Reaction time

Works while engine is running

Technical data

Physical state: liquid

Colour: clear/colourless

Odour: characteristic

Flashpoint: ~70 °C (DIN EN ISO 2719)

Density at 68 °F: 0,88 g/cm³ (DIN 51757)

Water resistant

Available sizes	Item no.	PU
250ml	43934	24



Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.



Made in Germany

CTP GmbH
Saalfelder Straße 35 h

07338 Leutenberg
Germany

Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22

www.bluechemgroup.com
www.ctp.de

15.08.2018