



PLA Fluorescent Green, 1.75 mm, 1 kg

3DP-PLA1.75-01-FG

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Vlastnosti

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

Packaging

Množství v kartonu, kusy
Velikost kartonu, CUM
Váha kartonu, kg
Individual package size LxWxH:
Carton size LxWxH:
Země původu
Čárkový kód (EAN)
Customs code

8
0.036
11.49
210x210x85 mm
540x440x230 mm
CN
8716309094757
3916909000

Specifikace

Material: PLA, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 330 m
Density at 21.5 °C: 1.25 g/cm³
Melt Flow Index at 10min, 2.16kg: 5
Melt Point: 190 220 °C
Heat-Deflection-Temperature at 0.455 MPa: 50 °C
Yield Strength at 5mm/min: 45 MPa
Impact Strength: 5 KJ/m²
Elongation at Break: 20 %
Diameter: 1.75 ± 0.05 mm

Systémové požadavky

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Certifikát

