Cololight®

Setting up your Cololight PLUS User Guide V1.0

PRODUCT INTRODUCTION

scenes with various experiences.

LifeSmart Cololight PLUS is an ambient light supporting split joint and color changing. It can be placed on the table or installed as background wall, suspended ceiling.

Cololight PLUS is HomeKit-enabled, you can use Siri and Home app on iOS devices to control it.

Its unique functions like changing color with music,

voice control bring intelligent playing into lighting system, providing dining, living and so many other



Reset method: Press and hold the reset hole until the green indicator light on the controller flashes. Release the button and the device will reboot. Wait about 10 seconds for the device to reboot successfully and complete the reset.

FEATURES

· Creative Shape

Hexagon design, seamless connection and no dark area on the surface.

FIIN of DIV

various shapes with gorgeous effects to creates joyful atmosphere.

. Color Changing with Music

Dynamic effects & Sound activated.

• 16 Million Colors

3 color selection modes (Selected, Dynamic & Customized).

FEATURES

App Control

Various playing methods, Dimmable function, Auto ON/OFF.

Intelligent Scene Linkage

Auto lighting up when opening door (Should be used with sensor).

Voice Control

support Siri & Amazon Alexa & Google Assistant.

No Hub Required

Directly controlled through App on mobile device.

SPECIFICATIONS

Light size 86x74.5x30.5mm Light weight 52.5g Controller Size 46.5x30.5x28mm Controller weight 54g Power cable length 1m Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not support Input Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5~90% Material ABS/ABS+PC				
Light weight 52.5g Controller Size 46.5x30.5x28mm Controller weight 54g Power cable length 1m Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not supports) Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5-90%				
Controller Size 46.5x30.5x28mm Controller weight 54g Power cable length 1m Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not supports Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5-90%	Light size	86x74.5x30.5mm		
Controller weight 54g Power cable length 1m Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not support of	Light weight	52.5g		
Power cable length 1m Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not support Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5-90%	Controller Size	46.5x30.5x28mm		
Communication protocol Wi-Fi Operating frequency 2.4GHz (5GHz not support Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5-90%	Controller weight	54g		
Operating frequency 2.4GHz (5GHz not support Input 5V DC, 2A Operating temperature -5–45°C Operating humidity 5–90%	Power cable length	1m		
Input 5V DC, 2A Operating temperature -5-45°C Operating humidity 5-90%	Communication protocol	Wi-Fi		
Operating temperature -5~45°C Operating humidity 5~90%	Operating frequency	2.4GHz (5GHz not supported)		
Operating humidity 5~90%	Input	5V DC, 2A		
	Operating temperature	-5~45°C		
Material ABS/ABS+PC	Operating humidity	5~90%		
	Material	ABS/ABS+PC		
Power consumption Static 0.3W Maximal 5W	Power consumption	Static 0.3W Maximal 5W		
Control mode App/Voice/Control button	Control mode	App/Voice/Control button		

APP INSTRUCTION

Scan QR code or input following URL in your mobile browser to download App.

http://www.ilifesmart.com/getapp_qlgp.html

Visit the iOS App Store or Google Play and search for **Cololight**.


Pair up COLOLIGHT with your mobile device according to the instruction on App.




NOTE

Please check the FAQ in the Cololight App if you have any problems.


Use the CONNECTOR to fix the Controller unit PLUS and the Cololight



Use the CONNECTOR to connect the COLOLIGHTs together. One end of the CONNECTOR must connect to the outer slot while other end must connect to the inner slot.



Use FIXATORs to strengthen stability. Notice that FIXATOR must connect to single hole slots between two COLOLIGHTs. It only strengthens the structure without communication function.



NOTICE

- Controlling this HomeKit-enabled accessory automatically and away from home requires a HomePod, an Apple TV with tvOS 10.x or later, or an iPad with iOS 10.x or later set up as a home buth
- 2. Use of the Works with Apple HomeKit badge means that an electronic accessory has been designed to connect specifically to iPod touch, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.
- Home app does not support functions such as single LED edit, playing method create, please turn to Cololight App if required.

WARNING

This product contains small parts that can cause danger if swallowed by children.

This product is not suitable for children under the age of 3.



Children under the age of 14 must use this product under parental supervision.

Hazardous Substance Table

Part Name		Grey plastic shell	Code Label	IC Body
Harmful Substance	(Cd)	0	0	0
	(Pb)	0	0	0
	(Hg)	0	0	0
	(Cr)	0	0	0
	(Br)	0	0	0

This table is made according to IEC 62321 test standard.

- O Expresses that this hazardous substance in all homogeneous materials of this part is within limit range.
- X Expresses that this hazardous substance in at least one homogeneous material of this part is above limit.

WARRANTY DESCRIPTION

replacement.

Thank you for purchasing this LifeSmart product. In order to protect your rights, please read the following content carefully: The warranty period of our company's products is one year from the date of purchase or longer if local laws impose a longer minimum term, in which case the minimum term is the warranty period. During the warranty period, any faults caused by the product itself or for quality problems that arise under normal usage, LifeSmart will provide a free

ATTENTION

The following conditions are not covered by the warranty:

- Product failure or damage caused by installation, use, and maintenance that is not in accordance with the product instructions;
- · Products beyond the warranty period:
- Products that have the barcode tampered with or removed:
- Devices that have been tampered with or customized outside of LifeSmart Terms of Service as on the LifeSmart App and website:

ATTENTION

- User-caused damage, such as inappropriate voltage input, high temperature, accidental spillage, physical damage, etc;
- Product failure or damage caused by force majeure such as earthquakes, fires, or floods;
- Product failure or damage caused by other problems except the product itself.

User support e-mail address

support@ilifesmart.com

Website

www.ilifesmart.com



notice.

LifeSmart is a trademark of Hangzhou LifeSmart Technology Co., Ltd. As for the trademarks, product logos and product names from other companies presented within this manual, they are possessed by their own right holders. Without our written permission, no entity or individual shall extract, copy or disseminate in part or the whole of the manual contents in any form. Due to product version upgrades or other reasons, content of this manual may change. Our company reserves

the right to change the contents of this manual without any

This manual is used only for instructional purposes. We strive to provide accurate information in this manual, but we are not able to ensure that the content of this manual is current. Statements, information and advice in this manual do not constitute any expressed or implied assurance. Updated manuals are available on our website at www.ilifesmart.com or by contacting our team.

FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1) This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

NOTE: The grantee is not responsible for any changes or modifications not expressly approved by the party responsible for compliance. Such modifications could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a recidential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

1) Reorient or relocate the receiving antenna.

2) Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

4) Consult the dealer or an experienced radio/TV technician for help.

RE EXPOSURE STATEMENT

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body.

DECLARATION OF CONFORMITY

Hereby, LifeSmart declares that the radio equipment type Cololight is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address:

http://global.ilifesmart.com/ce/docs/



Notice: This device may be used in each member state in EU.

Address:10-11th Floor, Building A, SUPCON Information, 352 Binkang Road, Binjiang District, Hangzhou, Zhejiang, CHN

Copyright © 2020 LifeSmart Inc. All Rights Reserved.

Manufacturer: Hangzhou LifeSmart Technology Co., Ltd.

P/N: 88.005860 A1